Cat. No

Description

"UniFreez™ U" Smart-Lab™ ULT Freezer, 4 & 5-Inner Door, Upright-type, -86 °C ~-65 °C Non-Freon Refrigerants, Auto Vacuum Releasing System, 393-/503-/714-/796-Lit, Wire™ Service 초저온 냉동고, 업라이트형, 단일 냉각 시스템, 터치 스크린 LCD 컨트롤러, 친환경 냉매 채용



SMART Ultra-Low Temperature Freezer, "UniFreez™ U800"

>>> Smart-Lab™ Controller



7" Full Touch Screen TFT LCD



It is possible to monitor and control the Smart-Lab™ equipment through all smart phone, tablet without restraint of time and place.

Controlled by Smart-Phone

- UL/CUL & CE Certified ■ Made in Korea
- PL(Product Liability) Insurance ■ GD(Good Design)-mark
- with Certificate & Traceability: Controlled by Serial Number, Certificate, Delivery-information, and Traceable Data Base System
- "UniFreez™ U" System can freeze down to -86°C: realize robust and long life time.
- Smart-Lab™ Controller: Remote Controlled by Smart-Phone with WiRe™ App Service
- Ergonomic 7" Full Touch Screen TFT LCD
- Easy Monitoring and Control Eye level Controller
- Internet Connectivity with WiFi
- Storage Management & Automatic Temp. Data Recording
- Self-Diagnostic Function: Built in Standard Warning and Alarm Functions
- RS232 Communication Link
- * Easy Maintenance and Improved Performance
- * High-quality Insulation Panel and Inner Doors ensure defrosting around outer surface.
- * Automatic Vacuum Breaker Easy to re-open the Door.
- * Robust & Flexible design of Door Handle
- * Use of Block Condenser removes filter and causes of related failure.
- * Filter-free Mechanism lowers heat generated by the compressor
- * CFC-free Refrigerants are used
- * External Temp. Sensor Hole
- * Inner Door Height: 312mm(4 Door), 252mm(5 Door)
- * Included Shelves : 3ea.(4 Door), 4ea.(5 Door)

Specifications & Ordering information

Spec. Model		"UniFreez U400" 4 & 5 Door Max. Capa. 393L	"UniFreez U500" 4 & 5 Door Max. Capa. 503L	"UniFreez U700" 4 & 5 Door Max. Capa. 714L	"UniFreez U800" 4 & 5 Door Max. Capa. 796L	
Capacity			393 Lit.	503 Lit.	714 Lit.	796 Lit.
	Range		-86 ℃~-65 ℃ -80 ℃~-65 ℃			
Temp.			at Room Temperature of 30 ℃ and Humidity of 70%			
	Sensor		PT100 Sensor			
Compressor			Hermetic Type			
Condenser Type			Block Condenser, No Pin, Filter Free Mechanism			
Refrigerant			Natural (CFC Free Refrigerant System)			
Controller & Display			7" Full Touch Screen TFT LCD (Smart-Lab [™] Controller)			
Shelves			3ea.(4 Door), 4ea(5 Door)			
Max. Q'ty of Racks	4-Door		16pcs of 15(5×3)- Placed Rack (RFU4234)	16pcs of 20(5×4)- Placed Rack (RFU4257)	24pcs of 20(5×4)- Placed Rack (RFU4257)	28pcs of 20(5×4)- Placed Rack (RFU4257)
	5-Door		20pcs of 12(4×3)- Placed Rack (RFU5234)	20pcs of 16(4×4)- Placed Rack (RFU5257)	30pcs of 16(4×4)- Placed Rack (RFU5257)	35pcs of 16(4×4)- Placed Rack (RFU5257)
Material	Internal		Stainless-steel (#304)			
	External		Powder Coated steel Plate			
	Inner Door		Powder Coated Stainless-steel (#304)			
Chamber Dimension	Internal(mm)		600×500×1,310	600×640×1,310	880×620×1,310	980×620×1,310
(w×d×h)	External(mm)		840×750×1,900	840×890×1,900	1,120×870×1,900	1,220×870×1,900
Net Weight			210 kg	240 kg	320 kg	350 kg
Packing Size (w \times d \times h) (cm) & Gross Weight			116×116×222	116×124×222	140×140×221	150×140×221
			296 kg	327 kg	442 kg	472 kg
Power Consumption			373 w/h	458 w/h	503 w/h	588 w/h
Electrical Reqts.			1 Phase, AC 120V, 60Hz or AC 230V, 50 / 60Hz			
Cat. No.	4-Door	230V	DH.SWUF00400	DH.SWUF00500	DH.SWUF00700	DH.SWUF00800
		120V	DH.SWUF03400	DH.SWUF03500	DH.SWUF03700	DH.SWUF03800
Price, Each. ₩			8,070,000	8,912,000	10,997,000	13,081,000
Cat. No.	5-Door	230V	DH.SWUF00450	DH.SWUF00550	DH.SWUF00750	DH.SWUF00850
		120V	DH.SWUF03450	DH.SWUF03550	DH.SWUF03750	DH.SWUF03850
Price, Each. ₩			8,589,000	9,378,000	11,592,000	│ 13,808,000 ₩ 55,000별도!

* Other Specifications are available upon Customer's Request.

※ 운임 약 ₩ 55,000별도!

Optional Freezer Racks, Boxes, etc. : Please See 748~749 Page