

Multifunction Vortex Mixer Set "MaXshake VM30" with \$\$\phi\$76mm(3") Platform(PM110)





(1) Platform Head. φ76mm(3inch) "PM110" (Included)



(3) Microtube Platform Head, 0.5~2.0ml Tube "PM310" (Optional)



(Included)



(Included)

Made in Korea

다용도 볼텍스 믹서, 다양한 속도 조절, 인체공학적 디자인 적용, 강력하고 안정된 동작과 저소음

PL(Product Liability) Insurance

- with Certificate & Traceability : Controlled by Serial Number, Certificate, Delivery-information, and Traceable Data Base System
- Ideal for Mixing Solutions in Test Tubes or Small Flasks with Circular, Oscillating Movement
- Variable Speed Control Allows Slow Speed Shaking Action up to High Speed Vortexing
- * Gentle Mixing to Re-suspending Pellet * Ergonomic Design with Stable Low Profile Body.
- * A robust and sturdy diecast construction vortex mixer.
- * Exceptional stability on the bench thanks to the combination of weight and non-slip feet.
- * Variable speed up to 3,300rpm. * Continuous-run or touch-activated run modes.
- * Powerful motor for efficient mixing * Variable speed for gentle to vigorous mixing.
- * Circular orbit for an effective vortex at any speed
- * Constant torque within the full range of speed. * Eccentric with oil-less ball bearings
- * Optimized counter balance system minimizes vibration.
- * Counter balance design for minimal body vibration.
- * Special designed silicon feet absorb vibration at high speeds.
- * Speed Regulation through knob provided on the control panel
- * Electronic speed control for constant speed even during changes in load
- * Conical tube can be mixed smoothly by hand holding.
- * One mixing head for a variety of tube sizes
- * Universal Head for a variety of mixing applications
- * Accepting vessels up to 76mm diameter
- * MBR(Methyl Methacrylate Butadiene Rubber) feet for ultra stability and vibration damping

Specifications & Ordering information

Spec. Model		"MaXshake VM30"	
Speed Range		0 ~ 3,300 rpm	
Shaking Motion		Orbital, Circuit Orbit : 4.0mm	
Control		Analog Phase Controller	
Motor		Brushless AC Motor	
Head		included Pop-off Cup Head and ϕ 76mm Platform	
Max. Load		0.5kg	
Material		Aluminum Die-casting with Powder Coating	
Dimensions (w×d×h) (mm)		140 $ imes$ 190 $ imes$ h123 mm	
Weight		3 kg	
Others		3-position Power Switch Operates Aluminum Die-casting with Powder Coating included Pop-off Cup Head and ϕ 76mm Platform	
Packing Dimension (w×d×h) (mm)		175×255×h215 mm	
Gross Weight		3 kg	
Power Consumption		30 W	
Electrical Reqts.		1 Phase, AC 120V, 50 / 60Hz or AC 230V, 50 / 60Hz	
Cat. No.	230V, 60Hz	DH.WVM00030	
	230V, 50Hz	DH.WVM00031	
	120V, 60Hz	DH.WVM00032	
	120V, 50Hz	DH.WVM00033	
Price, Each. ₩		190,000	

* Other Specifications are available upon Customer's Request.

Spare Platform	Heads	Ea. Price, ₩
	 (1) Platform Head, "PM110", <i>Φ</i>76mm(3inch) (2) Pop-off Cup Head, "PM210" 	11,000 19,000
Optional Platfo	orm Heads	Ea. Price.₩

19,000

DH.WVM00310 (3) Microtube Platform Head(0.5~2.0ml), "PM310"